



GLRD für Alfa Laval® SSP SR Serie

Seals to suit Alfa Laval® SSP SR Series

Pumpe Style	d1 mm	d3 mm	d7 mm	l3 mm	l4 mm
SR1	20,00	32,40	30,00	20,00	10,70
SR2	30,00	44,00	41,30	21,40	10,90
SR3	35,00	50,80	47,00	22,00	12,20
SR4	45,00	62,40	58,30	22,90	11,60
SR5	55,00	76,00	69,60	29,30	13,00
SR6	75,00	99,20	92,20	31,10	14,50

**Eigenschaften:**

Einzel-Gleitringdichtung  
Drehrichtungsunabhängig  
Nichtentlastet

**Einsatzgrenzen:**

Druck  $p = 17 \text{ bar}$   
Geschwindigkeit  $v = 18 \text{ m/s}$   
Temperatur  $t = -20 +220^\circ\text{C}$   
(Elastomerbedingt)

**Komponenten:**

Gleitring SiC, TC  
Gegenring SiC, TC  
Nebendichtung PTFE, NBR, EPDM, VITON®  
Feder 1.4301  
Sonstige Teile 1.4301

**Characteristics:**

Single Spring Seal  
Double Directional  
Unbalanced

**Limit of applications:**

Pressure  $p = 17 \text{ bar (240 psi)}$   
Speed  $v = 18 \text{ m/s}$   
Temperature  $t = -20 +220^\circ\text{C}$   
(according to the rubber)

**Components:**

Rotary SiC, TC  
Stationary SiC, TC  
Secondary Seal PTFE, NBR, EPDM, VITON®  
Spring SS304  
Other Parts SS304



Serie BB7K-AL2